

YOREDALE

Sustainable, soft British wool fabric inspired by nature.

Yoredale is a wool fabric with a modern range of colors. The fabric feels soft and cosy and is perfect for creating a classic, warm and inviting interior.

ABRASION (MARTINDALE) (Hard wear domestic use 25.000) 90.000 PILLING 4 scala 1-5 LIGHT FASTNESS 5 scala 1-8 COLOUR FASTNESS DRY 4 scala 1-5 COLOUR FASTNESS WET 4 scala 1-5 CIGARETTE TEST pass

Composition: 95 % Wool, 3 % Polyester, 2 % Polyamide

Price group: 5

Maintenance and cleaning

We recommend to vacuum the furniture regularly and wipe the surface with a damp cloth as needed. Remove spills immediately. If stains and dirt cannot easily be removed with a damp cloth, a cleaning machine for furniture and carpets can be used with lukewarm water. Make sure to use as little water as possible. Please follow the machine and cleaning agents instructions carefully. Pilling is a natural occurence on products which are made of natural fibres, such as wool. The pilling will reduce over time and can easily be removed with vacuuming or a "fabric-shaver". We do not recommend impregnation of our wool fabrics.





Read more about our fabrics.

Fabrics

We are uncompromising when it comes to fabric quality, and we cooperate with suppliers that manufacture in accordance with strict quality and environmental requirements. If correctly maintained, the fabrics we have selected will help give the furniture a long life. All our upholstery fabrics meet and exceeds the requirements of mobelfakta.no for Hard Wear. To meet Hard Wear requirements, the fabric must pass international tests for durability, light fastness, pilling resistance, fire safety and colour fastness. Tested in accordance with ISO 105-B02 (Light fastness) EN-12947-2, Martindale (wear test), and with ISO 12945-2 (pilling) and ISO 105x12 (rubbing/dye, wet and dry) and BS 5852 source 0&1(Fire safety test).



Extra Durable



More responsible fabrics Natural fabrics Oeko-Tex/Ecolabel



Flame resistant IMO Part 8 compliant BS 5852: Part 1:1979 s. 0&1